

[illegible]

STANDARD INSTRUMENT ARRIVAL ROUTES - RNAV (GNSS) RWY08L/08R

GENERAL: Surveillance service shall be available.
Maximum IAS below 10000' - 250 KT or by ATC.

NOTE: Flocks of birds in the vicinity of aerodrome.

Path Descriptor	WPT Identifier	Fly- over	Course/Track, ° M (T)	Magnetic variation	Distance (NM)	Turn direction	Altitude (FT)	Speed limit (KT)	Navigation specification	Remarks
LEPVO 2M										
IF	LEPVO	-	-	+5.7	-	-	+FL160	-	RNAV1	
TF	LELBA	-	290 (295.4)	+5.7	16.4	-	+A13000	-	RNAV1	
TISIB 2M										
IF	TISIB	-	-	+5.7	-	-	-FL160 +FL150	-	RNAV1	
TF	TT235	-	236 (241.7)	+5.7	11.0	-	+FL150	-	RNAV1	
TF	LELBA	-	236 (241.6)	+5.7	12.1	-	+A13000	-	RNAV1	
COMMON										
IF	LELBA	-		+5.7		-	+A13000		RNAV1	
TF	TT217	-	266 (271.1)	+5.7	5.7	L	-	-	RNAV1	
TF	TT218	-	266 (271.0)	+5.7	6.0	-	+A10000	-	RNAV1	
TF	TT219	-	266 (270.9)	+5.7	6.0	-	-	-	RNAV1	
TF	TT220	-	266 (270.8)	+5.7	6.0	-	-	-	RNAV1	
TF	TT221	-	265 (270.8)	+5.7	6.0	-	-A9000	-	RNAV1	
TF	ERWET	-	265 (270.7)	+5.7	6.0	-	+A7000	-	RNAV1	
TF	TT223	-	346 (351.6)	+5.7	5.0	R	+A6000	-	RNAV1	
TF	TP203	-	010 (015.9)	+5.7	12.1	R	+A4000	-	RNAV1	

Path Descriptor	WPT Identifier	Fly- over	Course/Track, ° M (T)	Magnetic variation	Distance (NM)	Turn direction	Altitude (FT)	Speed limit (KT)	Navigation specification	Remarks
BAMGU 2M										
IF	BAMGU	-		+5.7		-	+A13000		RNAV1	
TF	ERWET	-	022 (028.0)	+5.7	23.7	-	+A7000	-	RNAV1	
TF	TT223	-	346 (351.6)	+5.7	5.0	R	+A6000	-	RNAV1	
TF	TP203	-	010 (015.9)	+5.7	12.1	R	+A4000	-	RNAV1	

Path Descriptor	WPT Identifier	Inbound course °M (°T)	Turn direction	Minimum altitude (FT)	Maximum altitude (FT)	Speed limit (KT)	Magnetic variation	Navigation specification	Remarks
Hold	ERWET	305 (310.4)	L	A7000	-	-	+5.7	RNAV1	1min 00sec at or below 13000' 1min 30sec at or above FL150