

**TASHKENT/UZTP  
VOSTOCHNY  
RNAV (GNSS) RWY26**

DIBAD 2T, DOSOR 2T,  
MIKNO 2T, NIMAG 2T,  
OGRIP 2T, KUFIM 2T.



## STANDARD INSTRUMENT ARRIVAL ROUTES - RNAV (GNSS) RWY26

GENERAL: Surveillance service shall be available.  
Maximum IAS below 10000 - 250 KT or by ATC.

NOTE: Flocks of birds in the vicinity of aerodrome.

## DIBAD 2T

| Path Descriptor | WPT Identifier | Fly-over | Course/Track °M (°T) | Magnetic Variation | Distance (NM) | Turn Direction | Altitude (FT) | Speed Limit (KT) | Navigation Specification | Remarks |
|-----------------|----------------|----------|----------------------|--------------------|---------------|----------------|---------------|------------------|--------------------------|---------|
| IF              | DIBAD          | -        | -                    | -                  | -             | -              | +FL210        | -                | RNAV 1                   |         |
| TF              | TT231          | -        | 076 (081.9)          | +5.7               | 39.1          | -              | +A11000       | -                | RNAV 1                   |         |
| TF              | MEWOW          | -        | 141 (146.5)          | +5.7               | 6.0           | R              | -             | -                | RNAV 1                   |         |
| TF              | TT225          | -        | 125 (130.1)          | +5.7               | 14.2          | L              | +A8000        | -                | RNAV 1                   |         |
| TF              | TT226          | -        | 076 (081.4)          | +5.7               | 6.0           | L              | -             | -                | RNAV 1                   |         |
| TF              | KATXI          | -        | 076 (081.5)          | +5.7               | 7.9           | -              | -             | -                | RNAV 1                   |         |
| TF              | RUDWU          | -        | 076 (081.6)          | +5.7               | 5.8           | -              | +A4000        | -                | RNAV 1                   |         |

## DOSOR 2T

| Path Descriptor | WPT Identifier | Fly-over | Course/Track °M (°T) | Magnetic Variation | Distance (NM) | Turn Direction | Altitude (FT) | Speed Limit (KT) | Navigation Specification | Remarks |
|-----------------|----------------|----------|----------------------|--------------------|---------------|----------------|---------------|------------------|--------------------------|---------|
| IF              | DOSOR          | -        | -                    | -                  | -             | -              | +FL250        | -                | RNAV 1                   |         |
| TF              | TT228          | -        | 230 (235.7)          | +5.7               | 34.8          | -              | +FL150        | -                | RNAV 1                   |         |
| TF              | TT230          | -        | 141 (146.3)          | +5.7               | 12.0          | L              | -             | -                | RNAV 1                   |         |
| TF              | TT231          | -        | 141 (146.4)          | +5.7               | 6.0           | -              | +A11000       | -                | RNAV 1                   |         |
| TF              | MEWOW          | -        | 141 (146.5)          | +5.7               | 6.0           | -              | -             | -                | RNAV 1                   |         |
| TF              | TT225          | -        | 125 (130.1)          | +5.7               | 14.2          | L              | +A8000        | -                | RNAV 1                   |         |
| TF              | TT226          | -        | 076 (081.4)          | +5.7               | 6.0           | L              | -             | -                | RNAV 1                   |         |
| TF              | KATXI          | -        | 076 (081.5)          | +5.7               | 7.9           | -              | -             | -                | RNAV 1                   |         |
| TF              | RUDWU          | -        | 076 (081.6)          | +5.7               | 5.8           | -              | +A4000        | -                | RNAV 1                   |         |

## KUFIM 2T

| Path Descriptor | WPT Identifier | Fly-over | Course/Track °M (°T) | Magnetic Variation | Distance (NM) | Turn Direction | Altitude (FT) | Speed Limit (KT) | Navigation Specification | Remarks |
|-----------------|----------------|----------|----------------------|--------------------|---------------|----------------|---------------|------------------|--------------------------|---------|
| IF              | KUFIM          | -        | -                    | -                  | -             | -              | +FL160        | -                | RNAV 1                   |         |
| TF              | ZUGFO          | -        | 030 (035.1)          | +5.7               | 22.8          | -              | +A9000        | -                | RNAV 1                   |         |
| TF              | TT225          | -        | 076 (081.3)          | +5.7               | 6.0           | R              | +A8000        | -                | RNAV 1                   |         |
| TF              | TT226          | -        | 076 (081.4)          | +5.7               | 6.0           | -              | -             | -                | RNAV 1                   |         |
| TF              | KATXI          | -        | 076 (081.5)          | +5.7               | 7.9           | -              | -             | -                | RNAV 1                   |         |
| TF              | RUDWU          | -        | 076 (081.6)          | +5.7               | 5.8           | -              | +A4000        | -                | RNAV 1                   |         |

## MIKNO 2T

| Path Descriptor | WPT Identifier | Fly-over | Course/Track °M (°T) | Magnetic Variation | Distance (NM) | Turn Direction | Altitude (FT) | Speed Limit (KT) | Navigation Specification | Remarks |
|-----------------|----------------|----------|----------------------|--------------------|---------------|----------------|---------------|------------------|--------------------------|---------|
| IF              | MIKNO          | -        | -                    | -                  | -             | -              | +FL250        | -                | RNAV 1                   |         |
| TF              | TT228          | -        | 140 (146.1)          | +5.7               | 29.7          | -              | +FL150        | -                | RNAV 1                   |         |
| TF              | TT230          | -        | 141 (146.3)          | +5.7               | 12.0          | -              | -             | -                | RNAV 1                   |         |
| TF              | TT231          | -        | 141 (146.4)          | +5.7               | 6.0           | -              | +A11000       | -                | RNAV 1                   |         |
| TF              | MEWOW          | -        | 141 (146.5)          | +5.7               | 6.0           | -              | -             | -                | RNAV 1                   |         |
| TF              | TT225          | -        | 125 (130.1)          | +5.7               | 14.2          | L              | +A8000        | -                | RNAV 1                   |         |
| TF              | TT226          | -        | 076 (081.4)          | +5.7               | 6.0           | L              | -             | -                | RNAV 1                   |         |
| TF              | KATXI          | -        | 076 (081.5)          | +5.7               | 7.9           | -              | -             | -                | RNAV 1                   |         |
| TF              | RUDWU          | -        | 076 (081.6)          | +5.7               | 5.8           | -              | +A4000        | -                | RNAV 1                   |         |

Continued on the next page

## STANDARD INSTRUMENT ARRIVAL ROUTES - RNAV (GNSS) RWY26

## NIMAG 2T

| Path Descriptor | WPT Identifier | Fly-over | Course/Track °M (°T) | Magnetic Variation | Distance (NM) | Turn Direction | Altitude (FT) | Speed Limit (KT) | Navigation Specification | Remarks |
|-----------------|----------------|----------|----------------------|--------------------|---------------|----------------|---------------|------------------|--------------------------|---------|
| IF              | NIMAG          | -        | -                    | +5.7               | -             | -              | +FL250        | -                | RNAV 1                   |         |
| TF              | TT228          | -        | 218 (224.3)          | +5.7               | 28.9          | -              | +FL150        | -                | RNAV 1                   |         |
| TF              | TT230          | -        | 141 (146.3)          | +5.7               | 12.0          | L              | -             | -                | RNAV 1                   |         |
| TF              | TT231          | -        | 141 (146.4)          | +5.7               | 6.0           | -              | +A11000       | -                | RNAV 1                   |         |
| TF              | MEWOW          | -        | 141 (146.5)          | +5.7               | 6.0           | -              | -             | -                | RNAV 1                   |         |
| TF              | TT225          | -        | 125 (130.1)          | +5.7               | 14.2          | L              | +A8000        | -                | RNAV 1                   |         |
| TF              | TT226          | -        | 076 (081.4)          | +5.7               | 6.0           | L              | -             | -                | RNAV 1                   |         |
| TF              | KATXI          | -        | 076 (081.5)          | +5.7               | 7.9           | -              | -             | -                | RNAV 1                   |         |
| TF              | RUDWU          | -        | 076 (081.6)          | +5.7               | 5.8           | -              | +A4000        | -                | RNAV 1                   |         |

## OGRIP 2T

| Path Descriptor | WPT Identifier | Fly-over | Course/Track °M (°T) | Magnetic Variation | Distance (NM) | Turn Direction | Altitude (FT) | Speed Limit (KT) | Navigation Specification | Remarks |
|-----------------|----------------|----------|----------------------|--------------------|---------------|----------------|---------------|------------------|--------------------------|---------|
| IF              | OGRIP          | -        | -                    | +5.7               | -             | -              | +A12000       | -                | RNAV 1                   |         |
| TF              | ZUGFO          | -        | 067 (072.7)          | +5.7               | 42.1          | -              | +A9000        | -                | RNAV 1                   |         |
| TF              | TT225          | -        | 076 (081.3)          | +5.7               | 6.0           | R              | +A8000        | -                | RNAV 1                   |         |
| TF              | TT226          | -        | 076 (081.4)          | +5.7               | 6.0           | -              | -             | -                | RNAV 1                   |         |
| TF              | KATXI          | -        | 076 (081.5)          | +5.7               | 7.9           | -              | -             | -                | RNAV 1                   |         |
| TF              | RUDWU          | -        | 076 (081.6)          | +5.7               | 5.8           | -              | +A4000        | -                | RNAV 1                   |         |

| Path Descriptor | WPT Identifier | Inbound course °M (°T) | Turn direction | Minimum altitude (FT) | Maximum altitude (FT) | Speed limit (KT) | Magnetic variation | Navigation specification | Remarks                                                       |
|-----------------|----------------|------------------------|----------------|-----------------------|-----------------------|------------------|--------------------|--------------------------|---------------------------------------------------------------|
| Hold            | KATXI          | 076 (081.9)            | R              | A4000                 | -                     | -                | +5.7               | RNAV1                    | 1min 00sec at or below 13000'<br>1min 30sec at or above FL150 |
| Hold            | TT228          | 141 (146.3)            | R              | FL150                 | -                     | -                | +5.7               | RNAV1                    | 1min 00sec at or below 13000'<br>1min 30sec at or above FL150 |
| Hold            | TT231          | 141 (146.5)            | L              | A11000                | -                     | -                | +5.7               | RNAV1                    | 1min 00sec at or below 13000'<br>1min 30sec at or above FL150 |
| Hold            | DIBAD          | 076 (081.9)            | L              | FL210                 | -                     | -                | +5.7               | RNAV1                    | 1min 00sec at or below 13000'<br>1min 30sec at or above FL150 |
| Hold            | KUFIM          | 030 (035.1)            | R              | FL160                 | -                     | -                | +5.7               | RNAV1                    | 1min 00sec at or below 13000'<br>1min 30sec at or above FL150 |