

**TASHKENT/UZTP
VOSTOCHNY
RNAV (GNSS) RWY26**

LEPVO 2T, TISIB 2T.



STANDARD INSTRUMENT ARRIVAL ROUTES - RNAV (GNSS) RWY26

GENERAL: Surveillance service shall be available.
Maximum IAS below 10000 - 250 KT or by ATC.

NOTE: Flocks of birds in the vicinity of aerodrome.

LEPVO 2T

Path Descriptor	WPT Identifier	Fly-over	Course/Track °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed Limit (KT)	Navigation Specification	Remarks
IF	LEPVO	-	-	-	-	-	+FL160	-	RNAV 1	
TF	LELBA	-	290 (295.4)	+5.7	16.4	-	+A11000	-	RNAV 1	
TF	TT217	-	266 (271.1)	+5.7	5.7	L	-	-	RNAV 1	
TF	TT218	-	266 (271.0)	+5.7	6.0	-	+A10000	-	RNAV 1	
TF	TT219	-	266 (270.9)	+5.7	6.0	-	-	-	RNAV 1	
TF	TT220	-	266 (270.8)	+5.7	6.0	-	-	-	RNAV 1	
TF	TT221	-	265 (270.8)	+5.7	6.0	-	+A9000	-	RNAV 1	
TF	ERWET	-	265 (270.7)	+5.7	6.0	-	-	-	RNAV 1	
TF	TT223	-	346 (351.6)	+5.7	5.0	R	-	-	RNAV 1	
TF	ZUGFO	-	346 (351.6)	+5.7	6.9	-	-	-	RNAV 1	
TF	TT225	-	076 (081.3)	+5.7	6.0	R	+A8000	-	RNAV 1	
TF	TT226	-	076 (081.4)	+5.7	6.0	-	-	-	RNAV 1	
TF	KATXI	-	076 (081.5)	+5.7	7.9	-	-	-	RNAV 1	
TF	RUDWU	-	076 (081.6)	+5.7	5.8	-	+A4000	-	RNAV 1	

TISIB 2T

Path Descriptor	WPT Identifier	Fly-over	Course/Track °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed Limit (KT)	Navigation Specification	Remarks
IF	TISIB	-	-	-	-	-	+FL150	-	RNAV 1	
TF	TT235	-	236 (241.7)	+5.7	11.0	-	+A13000	-	RNAV 1	
TF	LELBA	-	236 (241.6)	+5.7	12.1	-	+A11000	-	RNAV 1	
TF	TT217	-	266 (271.1)	+5.7	5.7	R	-	-	RNAV 1	
TF	TT218	-	266 (271.0)	+5.7	6.0	-	+A10000	-	RNAV 1	
TF	TT219	-	266 (270.9)	+5.7	6.0	-	-	-	RNAV 1	
TF	TT220	-	266 (270.8)	+5.7	6.0	-	-	-	RNAV 1	
TF	TT221	-	265 (270.8)	+5.7	6.0	-	+A9000	-	RNAV 1	
TF	ERWET	-	265 (270.7)	+5.7	6.0	-	-	-	RNAV 1	
TF	TT223	-	346 (351.6)	+5.7	5.0	R	-	-	RNAV 1	
TF	ZUGFO	-	346 (351.6)	+5.7	6.9	-	-	-	RNAV 1	
TF	TT225	-	076 (081.3)	+5.7	6.0	R	+A8000	-	RNAV 1	
TF	TT226	-	076 (081.4)	+5.7	6.0	-	-	-	RNAV 1	
TF	KATXI	-	076 (081.5)	+5.7	7.9	-	-	-	RNAV 1	
TF	RUDWU	-	076 (081.6)	+5.7	5.8	-	+A4000	-	RNAV 1	

Path Descriptor	WPT Identifier	Inbound course °M (°T)	Turn direction	Minimum altitude (FT)	Maximum altitude (FT)	Speed limit (KT)	Magnetic variation	Navigation specification	Remarks
Hold	TT221	265 (270.7)	L	A9000	-	-	+5.7	RNAV1	1min 00sec at or below 13000' 1min 30sec at or above FL150
Hold	KATXI	076 (081.9)	R	A4000	-	-	+5.7	RNAV1	1min 00sec at or below 13000' 1min 30sec at or above FL150