

STATE WEATHER MINIMA FOR TAKE-OFF

RWY	ACFT CAT	RVR/VISIBILITY, m			
		EDGE LGTS, RCLL, RENL	EDGE LGTS, RENL, RCL MARKINGS	EDGE LGTS, RCL MARKINGS DAY ONLY	RWY MARKINGS DAY ONLY
08	A	125	250	250	500
	B				
	C				
	D	150	300	300	

STATE WEATHER MINIMA FOR LANDING

RWY	APCH TYPE	PARAMETER	APPROACH AND RWY LIGHTS	A	B	C	D
08	CAT III ILS	DA/(DH)	FULL	APPROVED			
		RA					
		RVR		75			
	CAT II ILS	DA/(DH)	FULL	1638 (100)			1658 (120)
		RA		111			131
		RVR		300			
	CAT I ILS	DA/(DH)	FULL	1738 (200)			
		RVR/VIS		550			
			ALS OUT	1200			
	LOC	MDA/(MDH)	FULL	2010 (472)			
		RVR/VIS		1500			
			ALS OUT	2200			
	RNP APCH (LNAV/VNAV)	DA/(DH)	FULL	1923 (385)	1935 (397)	1943 (405)	1953 (415)
		RVR/VIS		1100		1200	
			ALS OUT	1800		1900	
	RNP APCH (LNAV)	MDA/(MDH)	FULL	2473 (935)			
		RVR/VIS		3600			
			ALS OUT	4300			
	DVOR/DME	MDA/(MDH)	FULL	2620 (1082)			
		RVR/VIS		4100			
			ALS OUT	4900			

NOTES: 1. RA, DA, DH, MDA, MDH, CEILING - in feet;
 2. RVR, VIS - in metres;
 3. CIRCLE-TO-LAND IS PROHIBITED.

STATE WEATHER MINIMA FOR TAKE-OFF

RWY	ACFT CAT	RVR/VISIBILITY, m			
		EDGE LGTS, RCLL, RENL	EDGE LGTS, RENL, RCL MARKINGS	EDGE LGTS, RCL MARKINGS DAY ONLY	RWY MARKINGS DAY ONLY
26	A	125	250	250	500
	B				
	C				
	D	150	300	300	

STATE WEATHER MINIMA FOR LANDING

RWY	APCH TYPE	PARAMETER	APPROACH AND RWY LIGHTS	A	B	C	D
26	CAT III ILS	DA/(DH)	FULL	APPROVED			
		RA					
		RVR		75			
	CAT II ILS	DA/(DH)	FULL	1683 (100)			1703 (120)
		RA		88			108
		RVR		300			
	CAT I ILS	DA/(DH)	FULL	1783 (200)			
		RVR/VIS		550			
			ALS OUT	1200			
	LOC	MDA/(MDH)	FULL	1833 (250)			
		RVR/VIS		550			
			ALS OUT	1300			
	RNP APCH (LNAV/VNAV)	DA/(DH)	FULL	1952 (369)	1965 (382)	1973 (390)	1983 (400)
		RVR/VIS		1000	1100		
			ALS OUT	1700	1800		
	RNP APCH (LNAV)	MDA/(MDH)	FULL	2062 (479)			
		RVR/VIS		1500			
			ALS OUT	4300			
	DVOR/DME	MDA/(MDH)	FULL	2380 (797)			
		RVR/VIS		3000			
			ALS OUT	3600			

NOTES: 1. RA, DA, DH, MDA, MDH, CEILING - in feet;
2. RVR, VIS - in metres;
3. CIRCLE-TO-LAND IS PROHIBITED.