

STATE WEATHER MINIMA FOR TAKE-OFF

RWY	ACFT CAT	RVR/VISIBILITY, m			
		EDGE LGTS, RCLL, RENL	EDGE LGTS, RENL, RCL MARKINGS	EDGE LGTS, RCL MARKINGS DAY ONLY	RWY MARKINGS DAY ONLY
08L/26R	A	125	250	250	500
	B				
	C				
	D	150	300	300	

STATE WEATHER MINIMA FOR LANDING

RWY	APCH TYPE	PARAMETER	APPROACH AND RWY LIGHTS	ACFT CATEGORY			
				A	B	C	D
08L	CAT II ILS	DA/(DH)	FULL	1469/(100)			
		RA		105			
		RVR/VIS		300			
	CAT I ILS	DA/(DH)	FULL	1578/(209)	1591/(222)	1599/(230)	1609/(240)
		RVR/VIS		550			
			ALS OUT	1200			
	LOC	MDA/(MDH)	FULL	1810/(450)			
		RVR/VIS		1400			
			ALS OUT	2400			
	RNP APCH (LNAV/VNAV)	DA/(DH)	FULL	1684/(316)	1696/(328)	1704/(336)	1715/(347)
		RVR/VIS		750	800		900
			ALS OUT	1400	1500		1600
	RNP APCH (LNAV)	MDA/(MDH)	FULL	1810/(450)			
		RVR/VIS		1400			
			ALS OUT	2100			
	DVOR DME	MDA/(MDH)	FULL	1900/(540)			
		RVR/VIS		1700			
			ALS OUT	2400			
	RNAV VISUAL	MDA/(MDH)	DAY ONLY	2384 (970)		2484 (1070)	
		CEILING AGL		2300			
		VIS		5000			
26R	CAT I ILS	DA/(DH)	FULL	1613/(200)		1616/(202)	1626/(212)
		RVR/VIS		750		800	
			ALS OUT	1200			
	LOC	MDA/(MDH)	FULL	1880/(470)			
		RVR/VIS		1500			
			ALS OUT	2200			
	RNP APCH (LNAV/VNAV)	DA/(DH)	FULL	1707/(294)	1719/(306)	1727/(314)	1737/(324)
		RVR/VIS		750		800	
			ALS OUT	1400		1500	
	RNP APCH (LNAV)	MDA/(MDH)	FULL	1880/(470)			
		RVR/VIS		1500			
			ALS OUT	2200			
	DVOR DME	MDA/(MDH)	FULL	1934/(517)			
		RVR/VIS		1600			
			ALS OUT	2400			
	RNAV VISUAL	MDA/(MDH)	DAY ONLY	2384 (970)		2484 (1070)	
		CEILING AGL		2300			
		VIS		5000			

NOTES: 1. RA, DA, DH, MDA, MDH, CEILING - in feet;
 2. RVR, VIS - in metres;
 3. CIRCLE-TO-LAND IS PROHIBITED.

STATE WEATHER MINIMA FOR TAKE-OFF

RWY	ACFT CAT	RVR/VISIBILITY, m				
		EDGE LGTS, RCLL, RENL	EDGE LGTS, RENL, RCL MARKINGS	EDGE LGTS, RCL MARKINGS DAY ONLY	RWY MARKINGS DAY ONLY	
08R/26L	A	-	250	250	500	
	B					
	C		300	300		
	D					

STATE WEATHER MINIMA FOR LANDING

RWY	APCH TYPE	PARAMETER	APPROACH AND RWY LIGHTS	ACFT CATEGORY			
				A	B	C	D
08R	CAT I ILS	DA/(DH)	FULL	1569/(200)	1573/(204)	1581/(212)	1591/(222)
		RVR/VIS		750		800	
			ALS OUT	1200			
	LOC	MDA/(MDH)	FULL	1810/(450)			
		RVR/VIS		1400			
			ALS OUT	2100			
	RNP APCH (LNAV/VNAV)	DA/(DH)	FULL	1684/(316)	1696/(328)	1704/(336)	1715/(347)
		RVR/VIS		800			900
			ALS OUT	1400	1500		1600
	RNP APCH (LNAV)	MDA/(MDH)	FULL	1810/(450)			
		RVR/VIS		1400			
			ALS OUT	2100			
	DVOR DME	MDA/(MDH)	FULL	1900/(540)			
		RVR/VIS		1700			
			ALS OUT	2400			
	RNAV VISUAL	MDA/(MDH)	DAY ONLY	2384 (970)		2484 (1070)	
		CEILING AGL		2300			
		VIS		5000			
26L	RNP APCH (LNAV/VNAV)	DA/(DH)	FULL	1707/(294)	1719/(306)	1727/(314)	1737/(324)
		RVR/VIS		1200			1300
			ALS OUT	1400			1500
	RNP APCH (LNAV)	MDA/(MDH)	FULL	1890/(480)			
		RVR/VIS		2000			
			ALS OUT	2200			
	DVOR DME	MDA/(MDH)	FULL	1934/(517)			
		RVR/VIS		2100			
			ALS OUT	2400			
	RNAV VISUAL	MDA/(MDH)	DAY ONLY	2484 (1070)		2584 (1170)	
		CEILING AGL		2300			
		VIS		5000			

NOTES: 1. RA, DA, DH, MDA, MDH, CEILING - in feet;
2. RVR, VIS - in metres;
3. CIRCLE-TO-LAND IS PROHIBITED.