

STATE WEATHER MINIMA FOR TAKE-OFF

RWY	ACFT CAT	RVR/VISIBILITY, m			
		EDGE LGTS, RCLL, RENL, RVR	EDGE LGTS, RENL, RCL MARKINGS	EDGE LGTS, RCL MARKINGS DAY ONLY	RWY MARKINGS DAY ONLY
07/25	A	125	250	250	500
	B				
	C				
	D	150	300	300	

STATE WEATHER MINIMA FOR LANDING

RWY	LDG SYS	PARAMETER	APPROACH AND RWY LIGHTS	A	B	C	D
07	CAT II ILS	RA/ DA/(DH)	FULL	104'/1218'/(100')			
		RVR		300			
	CAT I ILS	DA/(DH)	FULL	1318'/(200')			
		RVR		550			
		RVR/VIS	RCLL OUT	750			
		RVR/VIS	ALS OUT	1200			
	RNP APCH (LNAV/VNAV)	DA/(DH)	FULL	1368'/(250')			1373'/(255')
		RVR		550			600
		RVR/VIS	RCLL OUT	800			
	RNP APCH (LNAV)	RVR/VIS	ALS OUT	1300			
		MDA/(MDH)	FULL	1430'/(312')			
		RVR		700			
		RVR/VIS	RCLL OUT	1000			
		RVR/VIS	ALS OUT	1400			
	RVR/VIS	ALS OUT PAPI OUT	2400				
	LOC	MDA/(MDH)	FULL	1500'/(382')			
		RVR		1100			
		RVR/VIS	RCLL OUT	1400			
		RVR/VIS	ALS OUT PAPI OUT	1800			
	VOR DME	MDA/(MDH)	FULL	1550'/(382')			
		RVR		1300			
		RVR/VIS	RCLL OUT	1600			
		RVR/VIS	ALS OUT	2000			
	VISUAL MANEUVERING (CIRCLING)	RVR/VIS	ALS OUT PAPI OUT	2400			
		MDA/(MDH)	DAY ONLY	1570'/(452')	1640'/(522')	1740'/(622')	1840'/(722')
CEILING AGL		1200'		1500'			
VIS	5000						

REMARK: RA, DA, DH, MDA, MDH - in feet. VIS, RVR, CMV - in metres.

STATE WEATHER MINIMA FOR LANDING

RWY	LDG SYS	PARAMETER	APPROACH AND RWY LIGHTS	A	B	C	D
25	CAT II ILS	RA/ DA/(DH)	FULL	107'/(1240')/(100')			
		RVR		300			
	CAT I ILS	DA/(DH)	FULL	1340'/(200')			
		RVR		RCLL OUT	550		
		RVR/VIS	ALS OUT	750			
			1200				
	RNP APCH (LNAV/VNAV)	DA/(DH)	FULL	1390'/(250')		1396'/(256')	1406'/(266')
		RVR		550		600	
		RVR/VIS	RCLL OUT	800			900
			ALS OUT				1300
	RNP APCH (LNAV)	MDA/(MDH)	FULL	1500'/(360')			
		RVR		900			
		RVR/VIS	RCLL OUT	1200			
			ALS OUT	1600			
			ALS OUT PAPI OUT	2400			
	LOC	MDA/(MDH)	FULL	1500'/(360')			
		RVR		900			
		RVR/VIS	RCLL OUT	1200			
			ALS OUT	1600			
			ALS OUT PAPI OUT	2400			
	VOR DME	MDA/(MDH)	FULL	1580'/(440')			
		RVR		1300			
		RVR/VIS	RCLL OUT	1600			
			ALS OUT	2000			
			ALS OUT PAPI OUT	2400			
	VISUAL MANEUVERING (CIRCLING)	MDA/(MDH)	DAY ONLY	1570'/(430')	1640'/(500')	1740'/(600')	1840'/(700')
		CEILING AGL		1200'		1500'	
VIS		5000					

REMARK: RA, DA, DH, MDA, MDH - in feet. VIS, RVR, CMV - in metres.