

STATE WEATHER MINIMA FOR TAKE-OFF

RWY	ACFT CAT	RVR/VISIBILITY, m			
		EDGE LGTS, RCLL, RENL, RVR	EDGE LGTS, RENL, RCL MARKINGS	EDGE LGTS, RCL MARKINGS DAY ONLY	RWY MARKINGS DAY ONLY
07/25*	A	-	250	250	500
	B				
	C				
	D	-	300	300	

RWY 07 IS PREFERABLE FOR DEPARTURE. IF UNABLE TO DEPART FROM RWY 07 DUE TO WEATHER OR ANOTHER TRAFFIC RWY 25 IS AVAILABLE FOR TAKE OFF.

*CLIMB GRADIENT OF 3,7% REQUIRED UP TO 2500'.
OTHERWISE TAKE-OFF MINIMA CEILING 2340' VIS 3000m WILL BE APPLIED FOR ALL ACFT TYPES.

STATE WEATHER MINIMA FOR LANDING

RWY	APCH TYPE	PARAMETER	APPROACH AND RWY LIGHTS	A	B	C	D
25	CAT I ILS	DA/(DH)	FULL	1228'/(200')			1232'/(204')
		RVR		750			
		VIS		1200			
	VOR DME	MDA/(MDH)	FULL	1600'/(572')			
		CMV		2200			
		VIS	ALS OUT	2600			
			ALS OUT PAPI OUT	2600			
		VISUAL MANEUVERING (CIRCLING)	MDA/(MDH)	DAY ONLY	1600'/(572')		1728'/(700')
	CEILING AGL		2700'				
	VIS		5000				
07	VOR DME	MDA/(MDH)	DAY ONLY	1440'/(426')			
		VIS		2400			
	VISUAL MANEUVERING (CIRCLING)	MDA/(MDH)	DAY ONLY	1586'/(572')		1714'/(700')	
		CEILING AGL		3000'			
		VIS		5000			

REMARK: DA, DH, MDA, MDH - in feet, RVR, CMV, VIS - in metres.