

STATE WEATHER MINIMA FOR TAKE-OFF

RWY	ACFT CAT	RVR/VISIBILITY, m				
		EDGE LGTS, RCLL, RENL, RVR	EDGE LGTS, RENL, RCL MARKINGS	EDGE LGTS, RCL MARKINGS DAY ONLY	RWY MARKINGS DAY ONLY	
04/22	A	-	250	250	500	
	B					
	C		300	300		
	D					

STATE WEATHER MINIMA FOR LANDING

RWY	APCH TYPE	PARAMETER	APPROACH AND RWY LIGHTS	A	B	C	D
04	CAT II ILS	RA/DA/(DH)	FULL	-			
		RVR		-			
	CAT I ILS	DA/(DH)	FULL	1781'(230')			
		RVR		550			
		VIS	RCLL OUT	800			
		VIS	ALS OUT	1200			
	RNP APCH (LNAV/VNAV)	DA/(DH)	FULL	1860'(309')			
		RVR		1200			
		VIS	ALS OUT	1400			
	RNP APCH (LNAV)	MDA/(MDH)	FULL	1950'(400')			
		RVR		1600			
		VIS	ALS OUT	1800			
			ALS OUT PAPI OUT	2400			
	LOC	MDA/(MDH)	FULL	1950'(395')			
		RVR		1100			
		VIS	ALS OUT	1800			
			ALS OUT PAPI OUT	2400			
	VISUAL MANEUVERING (CIRCLING)	MDA/(MDH)	DAY ONLY	2100'(549')		2320'(769')	
		CEILING AGL		1200'		1500'	
VIS		5000					
22	RNP APCH (LNAV/VNAV)	DA/(DH)	FULL	2050'(482')			
		RVR		-			
		VIS	ALS OUT	2300			
	RNP APCH (LNAV)	MDA/(MDH)	FULL	2120'(570')			
		RVR		-			
		VIS	ALS OUT	2600			
			ALS OUT PAPI OUT	2600			
	VISUAL MANEUVERING (CIRCLING)	MDA/(MDH)	DAY ONLY	2100'(532')		2320'(752')	
		CEILING AGL		1200'		1500'	
VIS		5000					

REMARK: RA, DA, DH, MDA, MDH, CEILING AGL - in feet. RVR, VIS - in metres.

INTENTIONALLY LEFT BLANK