

STATE WEATHER MINIMA FOR TAKE-OFF

RWY	ACFT CAT	RVR/VISIBILITY, m				
		EDGE LGTS, RCLL, RENL, RVR	EDGE LGTS, RENL, RCL MARKINGS	EDGE LGTS, RCL MARKINGS DAY ONLY	RWY MARKINGS DAY ONLY	
18/36	A	-	250	250	500	
	B					
	C		300	300		
	D					

STATE WEATHER MINIMA FOR LANDING

RWY	APCH TYPE	PARAMETER	APPROACH AND RWY LIGHTS	A	B	C	D
18	CAT I ILS	DA/(DH)	FULL	2132'/(208')		2151'/(227')	
		RVR		750		800	
		VIS	ALS OUT	1200			
	LOC	MDA/(MDH)	FULL	2645'/(721')			
		CMV		3000			
		VIS	ALS OUT	3600		3800	
			ALS OUT, PAPI OUT	3600		3800	
		2 NDB	MDA/(MDH)	FULL	2770'/(846')		
	CMV		3400				
	VIS		ALS OUT	4000		4200	
			ALS OUT, PAPI OUT	4000		4200	
	NDB	MDA/(MDH)	FULL	2770'/(846')			
		CMV		3400			
		VIS	ALS OUT	4000		4200	
		VIS	ALS OUT, PAPI OUT	4000		4200	

REMARK: DA, DH, MDA, MDH - in feet. RVR, CMV, VIS - in metres.