

STATE WEATHER MINIMA FOR TAKE-OFF

RWY	ACFT CAT	RVR/VISIBILITY, m				
		EDGE LGTS, RCLL, RENL, RVR	EDGE LGTS, RENL, RCL MARKINGS	EDGE LGTS, RCL MARKINGS DAY ONLY	RWY MARKINGS DAY ONLY	
15/33	A	-	250	250	500	
	B					
	C		300	300		
	D					

STATE WEATHER MINIMA FOR LANDING

RWY	APCH TYPE	PARAMETER	APPROACH AND RWY LIGHTS	A	B	C	D	
33	CAT I ILS	DA/(DH)	FULL	446'(201')		451'(206')	461'(216')	
		RVR		750			800	
		VIS	ALS OUT	1200				
	RNP APCH (LNAV/VNAV)	DA/(DH)	FULL	560'(315')	573'(328')	581'(336')	591'(346')	
		RVR		1000	1100		1200	
		VIS	ALS OUT	1400	1500		1600	
	RNP APCH (LNAV)	MDA/(MDH)	FULL	630'(381')				
		RVR		1400				
		VIS	ALS OUT	1800				
			ALS OUT PAPI OUT	2400				
	LOC	MDA/(MDH)	FULL	620'(371')				
		RVR		1300				
		VIS	ALS OUT	1700				
			ALS OUT PAPI OUT	2400				
	2 NDB	MDA/(MDH)	FULL	680'(431')				
		RVR		1600				
		VIS	ALS OUT	2000				
			ALS OUT PAPI OUT	2400				
	NDB	MDA/(MDH)	FULL	680'(431')				
		RVR		1600				
		VIS	ALS OUT	2000				
			ALS OUT PAPI OUT	2400				
	VISUAL MANEUVERING (CIRCLING)	MDA/(MDH)	DAY ONLY	750'(505')		940'(695')		
		CEILING AGL		1800'				
		VIS		5000				

REMARK: DA, DH, MDA, MDH, CEILING AGL - in feet. RVR, CMV, VIS - in metres.

STATE WEATHER MINIMA FOR LANDING

RWY	APCH TYPE	PARAMETER	APPROACH AND RWY LIGHTS	A	B	C	D
15	RNP APCH (LNAV/VNAV)	DA/(DH)	FULL	500'(253')		508'(261')	518'(271')
		RVR		800		900	
		VIS	ALS OUT	1300			
	RNP APCH (LNAV)	MDA/(MDH)	FULL	580'(331')			
		RVR		1300			
		VIS	ALS OUT	1500			
			ALS OUT PAPI OUT	2400			
	2 NDB	MDA/(MDH)	FULL	580'(331')			
		CMV/VIS		1300			
		VIS	ALS OUT	1500			
			ALS OUT PAPI OUT	2400			
	NDB	MDA/(MDH)	FULL	580'(331')			
		CMV/VIS		1300			
		VIS	ALS OUT	1500			
			ALS OUT PAPI OUT	2400			
	VISUAL MANEUVERING (CIRCLING)	MDA/(MDH)	DAY ONLY	750'(503')		940'(693')	
		CEILING AGL		1800'			
		VIS		5000			

REMARK: DA, DH, MDA, MDH, CEILING AGL - in feet. RVR, CMV, VIS - in metres.