

STATE WEATHER MINIMA FOR TAKE-OFF

RWY	ACFT CAT	RVR/VISIBILITY, m			
		EDGE LGTS, RCLL, RENL, RVR	EDGE LGTS, RENL, RCL MARKINGS	EDGE LGTS, RCL MARKINGS DAY ONLY	RWY MARKINGS DAY ONLY
13/31	A	-	250	250	500
	B				
	C		300	300	
	D				

STATE WEATHER MINIMA FOR LANDING

RWY	APCH TYPE	PARAMETER	APPROACH AND RWY LIGHTS	A	B	C	D
31	CAT I ILS	DA/(DH)	FULL	519'/(200')			
		RVR		750			
		VIS		1200			
	RNP APCH (LNAV/VNAV)	DA/(DH)	FULL	610'/(300')			
		RVR		900			
		VIS		1400			
	RNP APCH (LNAV)	MDA/(MDH)	FULL	680'/(360')			
		RVR		1200			
		VIS		1600			
	LOC	MDA/(MDH)	FULL	770'/(450')			
		RVR		1700			
		VIS		2100			
	2 NDB	MDA/(MDH)	FULL	770'/(450')			
		RVR		1700			
		VIS		2100			
	NDB	MDA/(MDH)	FULL	1140'/(820')			
		CMV		3400			
		VIS		3800			
	VISUAL MANEUVERING (CIRCLING)	MDA/(MDH)	DAY ONLY	1200'/(882')			
		CEILING AGL		2300'			
		VIS		5000			

REMARK: DA, DH, MDA, MDH, CEILING AGL - in feet. RVR, CMV, VIS - in metres.

STATE WEATHER MINIMA FOR LANDING

RWY	APCH TYPE	PARAMETER	APPROACH AND RWY LIGHTS	A	B	C	D
13	RNP APCH (LNAV/VNAV)	DA/(DH)	FULL	580'/(260')			
		RVR		1000			
		VIS		1300			
	RNP APCH (LNAV)	MDA/(MDH)	FULL	670'/(350')			
		RVR		1400			
		VIS	ALS OUT	1600			
			ALS OUT PAPI OUT	2400			
	2 NDB	MDA/(MDH)	FULL	700'/(380')			
		RVR		1500			
		VIS	ALS OUT	1700			
			ALS OUT PAPI OUT	2400			
	NDB	MDA/(MDH)	FULL	1140'/(820')			
		CMV		3400			
		VIS	ALS OUT	3800			
			ALS OUT PAPI OUT	4200			
	VISUAL MANEUVERING (CIRCLING)	MDA/(MDH)	DAY ONLY	1200'/(881')			
		CEILING AGL		2300'			
		VIS		5000			

REMARK: DA, DH, MDA, MDH, CEILING AGL - in feet. RVR, CMV, VIS - in metres.